



SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Euro-Polyester OT Spachtel
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Not determined
- · Application of the substance / the mixture Knife filler/ Surfacer
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Vosschemie GmbH Esinger Steinweg 50

D-25436 Uetersen

Phone: +49 (0)4122 717 0; Fax: +49 (0)4122 717158; info@vosschemie.de

· Further information obtainable from:

Abteilung Labor / +49 (0)4122 717 0

s.schaller@vosschemie.de

· 1.4 Emergency telephone number:

Giftinformationszentrum (GIZ)-Nord, Goettingen, Deutschland

Phone: +49 (0)551 19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 2)



Printing date 29.05.2015 V - 2 Revision: 29.05.2015

Trade name: Euro-Polyester OT Spachtel

(Contd. of page 1)



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xn; Harmful

R20-48/20-63: Harmful by inhalation. Harmful: danger of serious damage to health by prolonged

exposure through inhalation. Possible risk of harm to the unborn child.

Xi; Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.

R10: Flammable.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

GHS08

· Signal word Danger

· Hazard-determining components of labelling:

styrene

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H335 May cause respiratory irritation.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

(Contd. on page 3)





V-2Revision: 29.05.2015 Printing date 29.05.2015

Trade name: Euro-Polyester OT Spachtel

(Contd. of page 2)

25-50%

P260 Do not breathe mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 100-42-5 styrene EINECS: 202-851-5 🗙 Xn R20-48/20-63-65; 🗙 Xi R36/37/38

Reg.nr.: 01-2119457861-32 R10

Repr. Cat. 3 Flam. Liq. 3, H226; 🔕 Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412

· Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

Call a doctor immediately.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)





Printing date 29.05.2015 *V - 2 Revision:* 29.05.2015

Trade name: Euro-Polyester OT Spachtel

(Contd. of page 3)

 \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

· Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid contact with the eyes and skin.

Ensure adequate ventilation

Do not inhale gases / fumes / aerosols.

Keep away from ignition sources.

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.

Protect against electrostatic charges.

(Contd. on page 5)



V - 2 Printing date 29.05.2015 Revision: 29.05.2015

Trade name: Euro-Polyester OT Spachtel

(Contd. of page 4)

Use explosion-proof apparatus / fittings and spark-proof tools.

Ground/bond container and receiving equipment.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- · Information about storage in one common storage facility:

Store away from oxidising agents.

Store away from foodstuffs.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

Protect from heat and direct sunlight.

Keep ignition sources away - Do not smoke.

- · Recommended storage temperature: $< 30~^{\circ}C$
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:				
100-42-5 styrene				
WEL (Great Britain)	WEL (Great Britain) Short-term value: 1080 mg/m³, 250 ppm			
Long-term value: 430 mg/m³, 100 ppm				

· DNELs

100-42-5 styrene

100 0 5	·y. ••	
Oral	Long-term exposure - systemic effects	2.1 mg/kg bw/day (general population)
Dermal	Long-term exposure - systemic effects	343 mg/kg bw/day (general population)
		406 mg/kg bw/day (worker)
Inhalative	Acute/short-term exposure - local effects	182.75 mg/m³ (general population)
		$306 \text{ mg/m}^3 \text{ (worker)}$
	Acute/short-term exposure - systemic effects	174.25 mg/m³ (general population)
		289 mg/m³ (worker)
	Long-term exposure - systemic effects	10.2 mg/m³ (general population)
		85 mg/m³ (worker)

· PNECs

100-42-5 styrene

PNEC STP	5 mg/l (-)
PNEC aqua	0.028 mg/l (freshwater) 0.0028 mg/l (marine water)
	0.0028 mg/l (marine water)
	0.04 mg/l (intermittent releases)
PNEC sediment	0.614 mg/kg (freshwater)

0.0614 mg/kg (marine water)

PNEC soil 0.2 mg/kg (soil dw)

(Contd. on page 6)





Printing date 29.05.2015 *V - 2 Revision:* 29.05.2015

Trade name: Euro-Polyester OT Spachtel

(Contd. of page 5)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Do not eat, drink, smoke or sniff while working.

Store protective clothing separately.

After contact with skin, wash immediately with plenty of soap and water.

Take off contaminated clothing.

Use skin protection cream for skin protection.

· Respiratory protection:

Ensure good ventilation/exhaustion at the workplace.

Adhere to the workplace limit values and / or other threshold values.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Check the permeability prior to each anewed use of the glove.

Preventive skin protection by use of skin-protecting agents is recommended.

· Material of gloves

Fluorocarbon rubber (Viton)

Recommended thickness of the material: $\geq 0.7 \text{ mm}$

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level $\leq 6 \ (\geq 480 \ min)$

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Not suitable are gloves made of the following materials:

Natural rubber, NR

Chloroprene rubber, CR

Nitrile rubber, NBR

Butyl rubber, BR

PVC gloves

(Contd. on page 7)



Printing date 29.05.2015 V - 2 Revision: 29.05.2015

Trade name: Euro-Polyester OT Spachtel

(Contd. of page 6)

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

. 9	.1	Information	on	basic	physical	and	chemical	properties
_	• -	Injoi muutoit	0	UUSIU	pitysteat		Cit Cittle Cit	p. operites

· General Information

· Appearance:

Form: Pasty Colour: White

• Odour: Characteristic• pH-value: Not determined

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 145 °C

· Flash point: 31 °C

· Ignition temperature: 480 °C

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

 Lower:
 1.2 Vol %

 Upper:
 8.9 Vol %

· Vapour pressure at 20 °C: 6 hPa

• Density at 20 °C: $1 g/cm^3$

· Vapour density Not determined

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No decomposition if used according to specifications.

• 10.2 Chemical stability No decomposition if used and stored according to specifications.

(Contd. on page 8)



Printing date 29.05.2015 V - 2 Revision: 29.05.2015

Trade name: Euro-Polyester OT Spachtel

(Contd. of page 7)

· 10.3 Possibility of hazardous reactions

Reacts with peroxides and other radical forming substances.

Exothermic polymerisation.

· 10.4 Conditions to avoid

Protect from heat.

Avoid naked flames, sparks, other ignition sources and sunlight.

- \cdot 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Formation of toxic gases is possible during heating or in case of fire.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values relevant for classification:					
100-42-5 styrene					
Oral	LD50	5000 mg/kg (rat)			
Dermal	<i>LD50</i>	>2000 mg/kg (rat) (OECD 402)			

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.

· Subacute to chronic toxicity:						
100-42-5 s	100-42-5 styrene					
Inhalative	NOAEL (subacute)	0.85 mg/l (rat) (13w, 6h/day, Vapour)				
	NOAEL (subchronic)	0.8 mg/l (rat) (OECD 453, 2a, 6h/day, Vapour)				

· Additional toxicological information:

Inhalative LC50/4h 11.8 mg/l (rat)

May cause respiratory irritation.

Causes damage to the hearing organs through prolonged or repeated exposure.

- · Sensitisation No sensitising effects known.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Suspected of damaging the unborn child.

Repr. 2

Repr. 2							
· Carcinoge	· Carcinogenicity						
100-42-5 s	100-42-5 styrene						
Inhalative	NOAEL (carcinogeni	city) 4.34 n	ng/l (rat) (OECD 453, 2a, 6h/day, 5d/week, Vapour)				
· Reproduct	ive toxicity/Fertility						
100-42-5 s	tyrene						
Inhalative	NOAEL (fertility) 0.6	55 mg/l (rat,	parents) (OECD 416, Vapour)				
	0.22 mg/l (rat, F2) (OECD 416, Vapour)						
	2.2 mg/l (rat) (OECD 416, Parents, Vapour)						
· Reproduct	ive toxicity/Teratogen	icity					
100-42-5 s	100-42-5 styrene						
Inhalative	Inhalative NOAEL (developmental toxicity) 2.6 mg/l (rat)						
	NOAEL (teratogenici	ty)	2.6 mg/l (rat)				

(Contd. on page 9)



Printing date 29.05.2015 V - 2 Revision: 29.05.2015

Trade name: Euro-Polyester OT Spachtel

(Contd. of page 8)

LOAEL (maternally) 1.3 mg/l (rat)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:				
100-42-5 styrene				
EC10/96h	0.28 mg/l (Pseudokirchneriella subcapitata) (EPA OTS 797.1050)			
EC50/0.5h	≈500 mg/l (activated slugde) (OECD 209)			
EC50/48h	4.7 mg/l (daphnia magna) (OECD 202)			
EC50/72h	4.9 mg/l (Pseudokirchneriella subcapitata) (EPA OTS 797.1050)			
LC50/96h	4.02 mg/l (pimephales promelas)			
NOEC	1.01 mg/l (daphnia magna) (OECD-211 21d)			

· 12.2 Persistence and degradability

100-42-5 styrene

Biodegradation 70.9 % (activated slugde) (ISO DIN 9408, 28d, aerob)

· 12.3 Bioaccumulative potential

100-42-5 styrene

BCF 74 (-) (calculated) 13.5 (fish) log Kow 2.95 (-)

· Behaviour in environmental systems:

. 12.4 Mobility in soil 100-42-5 styrene Koc | 352 (-) log Koc | 2.55 (-)

- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste disposal key:

The waste codes given above are to be considered recommendations; because of regional and industrial sector specific features, application of different waste codes is possible.

(Contd. on page 10)





Trade name: Euro-Polyester OT Spachtel

(Contd. of page 9)

· European waste catalogue

07 02 08* other still bottoms and reaction residues

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informat	ion	
· 14.1 UN-Number		
· ADR, IMDG, IATA	UN1866	
· 14.2 UN proper shipping name		
ADR	1866 RESIN SOLUTION	
· IMDG, IATA	RESIN SOLUTION	
· 14.3 Transport hazard class(es)		
· ADR, IMDG, IATA		
3		
Class	3 Flammable liquids.	
· Label	3	
14.4 Packing group		
· ADR, IMDG, IATA	III	
14.5 Environmental hazards:	Not applicable.	
· 14.6 Special precautions for user	Warning: Flammable liquids.	
· EMS Number:	F-E, <u>S-E</u>	
14.7 Transport in bulk according to Anne	ex II of	
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:		
· ADR		
· Limited quantities (LQ)	5L	
· Tunnel restriction code	D/E	
· Remarks:	ADR 2.2.3.1.5	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · European regulations
- · Directive 2004/42/EC 2004/42/IIB (b) (250) <250
- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

(Contd. on page 11)





V-2Revision: 29.05.2015 Printing date 29.05.2015

Trade name: Euro-Polyester OT Spachtel

(Contd. of page 10)

- · Other regulations, limitations and prohibitive regulations Adhere to the Ordinances on the Prohibition of Certain Chemicals.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

	-				
H226		Flammable	liquid	and	vapour.

May be fatal if swallowed and enters airways. H304

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

R10 Flammable.

R20 Harmful by inhalation.

R36/37/38 Irritating to eyes, respiratory system and skin.

Harmful: danger of serious damage to health by prolonged exposure through inhalation. R48/20

R63 Possible risk of harm to the unborn child. R65 Harmful: may cause lung damage if swallowed.

· Department issuing MSDS: Abteilung Labor

- · Contact: Frau S. Schaller
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

* * Data compared to the previous version altered.